

Enterprise print solution

Highly productive, the new RICOH P 502 printer responds quickly to workgroup black and white print requirements, producing high quality office documents.

Impressive quality and performance:

- 1,200 x 1,200 dpi quality
- First page ready in under 5 seconds
- Fast 45 ppm (Letter)/43 ppm (A4) throughput
- Up to four paper trays

Ricoh's new state-of-the-art LED printer maintains exceptional speed, quality and reliability throughout long runs. Its powerful Intel® processor effortlessly processes complex jobs and eliminates bottlenecks, and the printer delivers its first 1,200 x 1,200 dpi print in under 5 seconds. Multi-page document sets are produced at a blistering 45 pages per minute.

Compact, quiet and economical:

- Space-saving design
- Low cost of ownership
- 17.4K pages starter toner



Optional paper trays enhance productivity. Envelopes, letterhead and forms can be fed automatically. In addition, with the printer switching seamlessly between trays, it need never run out of paper. Thanks to its compact design and quiet operation, the RICOH P 502 can be positioned on a desk or under a counter — within easy reach of workgroup users. With its smart energy saving features and high yield toner cartridges, the RICOH P 502 offers a low Total Cost of Ownership.

Secure desktop and mobile printing:

- PCL and PS3 print drivers
- iOS[™] and Android[™] support
- Confidential printing
- Enterprise-level security

Fast, easy to use and secured, the RICOH P 502 can meet ALL enterprise black and white print requirements. The intuitive PCL and PostScript® drivers simplify operation. Employees can print directly from their iOS™ and Android™ devices, and it is easy to password protect and lock confidential documents. Additionally, to safeguard business security, the intelligent platform supports the use of integrated workflow solutions — such as RICOH Streamline NX.



RICOH P 502

MAIN SPECIFICATIONS

GENERAL

Warm-up time 13 seconds

First output speed 4.3 seconds (A4 / LT SEF)

 Memory: standard
 2 GB

 HDD: option
 320 GB

 Duty cycle
 150K

Dimensions: W x D x H 14.76" x 16.22" x 12.24" (375 x 412 x 311 mm)

Weight: 42.5 lbs. (19.3 kg)
Power source 120-127V/12A 60Hz

PRINTER (STANDARD)

Printer language: standard PCL5e, PCL6, PostScript® 3™ (emulation), PDF direct (emulation)

Printer language: option IPDS, Genuine Adobe® PostScript® 3™, PDF Direct from Adobe®

Print resolution: maximum 1,200 x 1,200 dpi

Fonts: PCL 13 international fonts, 80 Roman fonts Fonts: PS3 (emulation) 13 international fonts, 80 Roman fonts

Network interface: standard

USB 2.0, Ethernet 10 base-T/100 base-TX/1000 base-T, USB 2.0 Host

Network interface: option

Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)

Mobile printing capability

Apple AirPrint™, Mopria®, NFC, RICOH Smart Device Connector

Network protocol TCP/IP (IP v4, IP v6)

Windows® environments Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016

Mac OS environments Macintosh OS X v10.10 or later
SAP® environments SAP® R3®, SAP® S/4®

Other supported environments NDPS Gateway, AS/400® using OS/400 Host Print Transform, Device Option Utility (Citrix), Linux environment, IBM iSeries

PAPER HANDLING

Paper input: standard 500 sheets
Paper input: maximum 2,100 sheets
Paper input: Bypass tray 100 sheets

Paper weight Paper tray(s): 14 - 58 lb. Bond (52 - 220 g/m²)
Optional paper tray(s): 14 - 58 lb. Bond (57 - 220 g/m²)

Optional paper tray(s): 14 - 58 lb. Bond (52 - 220 g/m²) Bypass tray: 14 - 68 lb. Bond (52 - 220 g/m²)

Paper types Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP

ENVIRONMENTAL SUSTAINABILITY

 Power consumption: Maximum (W)
 Less than 1,360 W

 Power consumption: TEC¹
 0.50 kWh

 ENERGY STAR®
 Certified

 EPEAT®
 Gold Rated*

* EPEAT Gold rating is applicable only in the USA.

PAPER HANDLING OPTIONS

 1x 250-sheet Paper Tray (PB 1110)
 Paper size: 5.5" x 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 1x 500-sheet Paper Tray (PB1120)
 Paper size: 5.5" x 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 1x 250-sheet Paper Tray (PB1110TL)
 Paper size: 5.5" x 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 1x 500-sheet Paper Tray (PB1120TL)
 Paper size: 5.5" x 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m²)

OTHER OPTIONS

Caster Table Type M34, VM Card Type P18, PostScript3 Unit Type P18, IPDS Unit Type P18, Hard Disk Drive Option Type P18, Medium Cabinet Type P, Tall Cabinet Type Q, IEEE802.11 Interface Unit Type M24, ESP XG-PCS-15D & ESP S1 Power Filter

¹ TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

RICOH P 502

MAIN SPECIFICATIONS

CONSUMABLES

Toner IM 430

17,400 prints

Consumable yield measuring method ISO/IEC 19752

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard Exton, PA 19341



1-800-63-RICOH



www.ricoh-usa.com

